

Link/2500i

Clever payment companion designed with integration in mind

- Specifically engineered for flexibility to accept all payment methods including NFC/Contactless, Apple Pay and Google Pay
- Reduce time to market by leveraging telium applications on a smart companion
- Designed to facilitate the integration with Ingenico's iCON Case and other third party devices



















The Link/2500i is PCI-PTS 5.x certified. Its Telium TETRA OS uses the latest cryptographic schemes with future-proof key length.

All payment options

In addition to EMV Chip & PIN and swipe, the Link/2500i supports the broadest range of contactless standards allowing NFC couponing and wallet use cases.

Designed for physical integration

The Link/2500i is the ideal product to integrate payment into Ingenico's iCON case and other third party devices. It is lightweight, features a slim design, as well as mechanical and electronic integration to charge and communicate with a third party device.

Seamless integration

The Link/2500i facilitates the in-store integration due to its agnosticity. Link/2500i can be paired with any iOS, Android or Windows-based tablet or smartphone to convert into a POS (point of sale) system.

User-friendly and intuitive interface

Featuring a cutting-edge design, the Link/2500i is user oriented with its bright 2.4" color display, and a mechanical keypad.









NAME			Link/2500i
Processor	Crypto and applications processor	Cortex A5	•
Memory	Internal	256MB Flash / 128MB RAM	•
OS	• • • • • • • • • • • • • • • • • • • •	Telium TETRA	•
Card Readers	Smart card	EMV Level 1, 50K lifespan	•
	Magstripe	ISO1/2/3, 100K lifespan	•
	Contactless	EMV / iS014443	•
Display	Size	2.4" color display, backlit, QVGA (240 x 320 pixels)	•
Keypad	Mechanical	20 keys, raised marking	•
Audio	Buzzer	Up to 50dB, adjustable	•
Terminal Connectivity	Bluetooth USB	Bluetooth 4.2 Class B Back connector for charging and USB data exchange	•
	Apple	Apple IAP Chip	•
Battery	Li-ion	600mAH	•
Terminal Size	LxWxH	129 x 70 x 13mm (5.07 x 2.75 x 0.51 inches)	•
Weight	Full-featured	120g (5.46oz)	•
Environment	Charging temperature	32°F to 104°F (0°C to +40°C)	•
	Operating temperature	14°F to 122°F (-10 to +50°C)	•
	Storage temperature	-4°F to 131°F (-20 to 55°C)	•
	Relative humidity, non-condensing	85% non-condensing at 104°F (40°C)	•
Security		PCI PTS 5.x online and offline certified	•
Accessories	iCON Case	USB Connection	•

