

Move/2500

Guarantee terminal availability whatever happens

- Assure terminal availability rate if power and network fail
- Make NFC payment a seamless consumer experience
- Robust and functional to meet merchants' daily needs



smartcard



magstripe



contactless



3G
GPRS
connectivity



ethernet



PSTN
connectivity



color display



TELIMUM
TETRA

The Move/2500 offers a seamless payment experience. A pocket-sized portable terminal, it complies with future security standards.

Highest security

The Move/2500 is PCI-PTS 4.x ready. Its TELIUM Tetra OS uses the latest cryptographic schemes with future-proof key length.

All payment options

The Move/2500 enables NFC couponing and wallet use cases, in addition to EMV Chip & PIN, swipe and contactless.

Designed for mobility

Designed for indoor and outdoor use, the Move/2500 Portable is a pocket-size and offers extended battery. It is the perfect business companion for merchants.

Guaranteed terminal availability

In a single terminal, the Move/2500 Hybrid comes with wired communication capabilities (Ethernet, PSTN) or wireless (3G, GPRS, Dual SIM). Then it guarantees terminal payment acceptance availability in case of network failures.

Seamless NFC payment


The Move/2500 boosts contactless payment by offering customers a seamless experience through a dedicated card-reader zone and faster transaction flow.

Secure payment from the TELIUM Tetra OS

Backed by 30 years of experience and with its user-friendly interface, the TELIUM Tetra Operating System embeds the best security mechanisms to protect transaction privacy and leverage Ingenico's unique portfolio of payment applications.

Eco-designed products

Ingenico Group adheres to a proactive eco-design policy. From design to production and market launch to recycling, we strive to minimize Ingenico's environmental footprint throughout product life cycles.



NAME			Move/2500 hybrid	Move/2500 portable
Processor	Application & Crypto processor	Cortex A5	●	●
Memory		128 MB RAM, 256 MB Flash 128 MB RAM, 512 MB Flash	● Option	● Option
SIM		2 SIM	Option	Option
SAM		2 SAM 3rd SAM	● Option	● Option
Card readers	Magstripe Smart card NFC/Contactless	ISO 1/2/3, 500K lifespan EMV Level 1, 500K lifespan EMV Level 1 compliant	● ● ●	● ● ●
Display	Color	2.4" backlit , QVGA (320x240 pixels)	●	●
Keypad		16keys, raised Marking, backlit 4 Functional Keys without backlight	● ●	● ●
Audio	Buzzer		●	●
Thermal Printer	Speed in lines/s Paper roll cage	Up to 24 lines/s 58 mm width x Ø 40mm	● ●	● ●
Terminal connectivity	WAN	3G and/or GPRS	Option	●
	Wired	Dial-up Modem RJ45 Ethernet 10/100 base T RJ45	● ●	x x
Terminal connections	USB Serial Power Supply	Micro USB Host & Slave RS 232 RJ11 Dedicated power jack	● ● ●	● x ●
Battery	Li-ion	2200mAh	●	●
Terminal size	Portable Hybrid	168x81x58 mm (6.6x3.2x2.3") 168x81x69 mm (6.6x3.2x2.7")	●	●
Weight	Terminal + Battery	320 g (11 oz)	●	●
Environment	Operating Temperature Storage Temperature Operating Humidity	-10°C to +40°C (14°F to 104°F) -20°C to +55°C (-4°F to 131°F) 85% non-condensing at +40°C(104°F)	● ● ●	● ● ●
Security		PCI PTS 4.1 Online & Offline ready	●	●



www.ingenico.com

ingenico
Smart
terminals