

Move/3500

Accept any payment while on-the-go

- Leverage Telium applications on the next-generation payment terminal
- Make NFC payment a seamless consumer experience
- Bring mobile payment to your POS with the most connected terminal



smartcard



magstripe



contactless



connectivity



large display



TELUM
TETRA

The Move/3500 offers a seamless payment experience while on-the-go. As a best-in-class, pocket-sized portable terminal it complies with future security standards.

Highest Security

The Move/3500 is PCI-PTS 4.x ready. Its TELIUM Tetra OS uses the latest cryptographic schemes with future-proof key length.

All Payment options

The Move/3500 enables NFC couponing and wallet use cases, in addition to EMV Chip & PIN, swipe and contactless.

User-friendly and intuitive interface

Featuring a large 3.2-inch display, the Move/3500 provides a seamless payment experience.

Designed for Mobility

Designed for indoor and outdoor use, the pocket-sized Move/3500 offers extended battery life. It is the perfect business companion for merchants.

Maximized network availability

In one single terminal, Move/3500 proposes a full spectrum wireless connectivity (with 3G, GPRS, Dual SIM, Bluetooth and WiFi), offering flexibility to merchant in the point of sale, while optimizing communication costs.

Seamless NFC payment


The Move/3500 boosts NFC payment by offering to customers a seamless experience through a dedicated card-reader zone and faster transaction flows.

Secure payment from the TELIUM Tetra OS

Backed by 30 years of experience and with its user-friendly interface, the TELIUM Tetra Operating System embeds the best security mechanisms to protect transaction privacy and leverage Ingenico's unique portfolio of payment applications.

Eco-designed products

Ingenico Group follows a proactive eco-design policy. From design to production, market launch to recycling, we strive to minimize Ingenico's environmental footprint throughout product life cycles.



NAME			Move/3500	
Processor	Application & Crypto processor	Cortex A5	●	
Memory	Internal	256 MB Flash, 128 MB RAM	●	
	External	512 MB Flash, 512 MB RAM MicroSD up to 32GB	Option ●	
OS		Telium Tetra OS	●	
SIM		2 SIM	Option	
SAM		2 SAM	●	
		3rd SAM	Option	
Card readers	Magstripe	ISO 1/2/3, 500K lifespan	●	
	Smart card Contactless	EMV Level 1, 500K lifespan EMV Level 1 compliant	Option ●	
Display	Color	3.2" display, backlit, QVGA (320x240 pixels)	●	
Keypad		20 keys, raised Marking, backlit	●	
Audio	Buzzer		●	
Data capture	GPS	GPS tracking	Option	
Thermal Printer	Speed in lines/s	up to 30 lines/s	●	
	Paper roll cage	58 mm width x Ø 40 mm	●	
Terminal connectivity	WAN	3G and/or GPRS	Option	
	LAN	WiFi and/or Bluetooth	Option	
	Multicom	WAN + LAN	Option	
Terminal connections	USB	Host & Slave	●	
	Power Supply	Dedicated power Jack	●	
Battery	Li-ion	2200mAh	●	
		2900mAh	Option	
Terminal size		169 x 78 x 57 mm (6.6x3.1x2.2")	●	
Weight	Terminal + Battery	320 g (11 oz)	●	
Environment	Operating Temperature	-10°C to +40°C (14°F to 104°F)	●	
	Storage Temperature	-20°C to +55°C (-4°F to 131°F)	●	
	Operating Humidity	85% non-condensing at +40°C (104°F)	●	
Accessory	Privacy shield	Factory Mounted	Option	
	Car Charger		Option	
	Docking-station	Charger		●
		2 RS232		Option
		USB Host		Option
		USB Slave		Option
		Modem		Option
	Ethernet 10/100 Base T		Option	
	Bluetooth		Option	
Security		PCI PTS 4.x Online & Offline ready	●	



www.ingenico.com

ingenico
Smart
terminals