
AECR C9 / AECR C5

A new generation of Android cash register combining payment





A large ecosystem of business apps

The AECR C9 or C5 take advantage of Android environment to enrich services at checkout thanks to the most open set of business applications on the market.

Global APIs

A single REST API across all Ingenico terminals to easily integrate payment and other services to the business app.

Business-centric user interface

Large 15.6" touchscreen display and powerful processing capabilities, the AECR C9 or C5 enhance customer interaction and accelerate the checkout.

Two form factors addressing all use cases

AECR C9

15.6"+15.6" version

			C9	C5
Processor	Application	ARM Cortex-A53 Octa Core, 2.0GHz	•	•
Memory	Internal External	• 16 GB Flash, 2 GB RAM • MicroSD up to 64GB	•	•
os	• For business apps	• Android 7.1 Secure OS	•	•
Merchant display	Color, Multi-touch Capacitive	• 15.6" 1920x1080 pixels	•	•
Customer display	• 15.6" version • 10.1" version	Color & capacitive multi- touch 1920x1080 pixels Color 1280x800 pixels	•	N/A N/A
Payment acceptance	Terminal connected thru cable or wirelessly	Telium TETRA (selected models) or APOS A8	•	•
Printer	Intergreted thermal printer	• 80 or 58mm width printer Diameter up to 80mm	•	N/A
Audio	Audio playback Audio Jack	• Speaker 10 Watts • 1	•	•
Connectivity		Bluetooth 4.2 WiFi 2.4GHz + 5GHz Ethernet	•	•

Merge ECR & payment

No pain, big game: AECR C9 or C5 can be bundled with any Telium TETRA or Android payment terminal allowing fast payment transaction capabilities.

Maximized countertop integration

Providing full-spectrum connectivity (Ethernet, USB Host and devices, Serial and cash drawer) as well as wireless 2.4GHz / 5GHz WiFi and Bluetooth, the AECR C9 or C5 offer the most flexible integration capability.

Compatible with Ingenico's suite of services

AECR C9/C5 is supported by Ingenico's Cloud services, from fleet management to merchant services such as business analytics and e-receipt management. In addition, Ingenico Customer Care Program insures payment availability, reliability and security on AECR C9/C5 during their entire life cycle.

The AECR C9 & AECR C5 are supported by our Cloud Services

AECR C5



			C9	C5
Connections	• 1 Micro USB OTG, 4 USB Host, 2 R5232, 1 RJ11 (for cash drawer), 1 RJ45 (for Ethernet), 1 Power port		•	•
Data capture	On customer side	• 5MP auto focus Camera, 1D / 2D Barcode scanning	•	N/A
Size	• AECR C9 (15.6"+15.6") • AECR C9 (15.6"+10.1") • AECR C5	• 380 x 225 x 390 mm (15.0 x 8.9 x 15.4") • 377 x 217 X 380 mm (14.8 x 8.5 x 14.9") • 376.5 x 340 x 177 mm (14.8 x 13.4 x 6.9")	• N/A	N/A N/A
Weight	• AECR C9 (15.6"+15.6") • AECR C9 (15.6"+10.1") • AECR C5	• 6.7Kg (236.3 oz) • 5.5Kg (194 oz) • 3.5Kg (123.5 oz)	e N/A	N/A N/A
Environment	Operating T° Storage T° Operating Humidity	• 0°C to +40°C (14°F to 122°F) • -20°C to +70°C (-4°F to 158°F) • 10% to 90% non-condensing	•	•

