

Desk/1000 series

Nimble design to boost checkout at the counter

- Expand payment options with both traditional and alternative payments
- Affordable and reliable PIN pad to enhance payment experience
- Part of the Desk/series offering a unified consumer-facing solution



The Desk/1000 series, a durable multi-payment acceptance solution bringing payment towards the customer.

Safe and secure payment

The Desk/1000 series is certified to the industry's highest security standards.

All payment options

The Desk/1000 series supports EMV chip & PIN, signature capture, and magstripe transactions, as well as the broadest range of contactless NFC, mobile wallet, and alternative payment methods thanks to an optional camera.

User-friendly and intuitive interface

Equipped with a clear contactless zone, a large keypad and an advanced consumer display, the Desk/1000 series enhances usability and accelerates the checkout.

Easy integration

Compact by design and robust, the Desk/1000 series fits easily on any counter.

Easy connectivity

With its USB connection, the Desk/1000 series can be connected to any Desk/series device and offers a unified consumer-facing solution. With its plug-and-play installation, the Desk/1000 series can easily be connected or disconnected.



NAME			Desk/1200	Desk/1500
Processor	Application & crypto processor	Cortex A5	●	●
Memory	Internal	128 MB Flash, 128 MB RAM 256 MB Flash, 128 MB RAM	Option	Option
OS		Telium TETRA	●	●
SAM		1 SAM	Option	N/A
Card readers	Magstripe Smart card Contactless	ISO 1/2/3, 500K lifespan EMV Level 1, 500K lifespan EMV Level 1 compliant	N/A N/A ●	● ●
Display	Colour Touchscreen	2.8" backlit, QVGA (320x240 pixels)	Option	N/A
Camera		2M pixels	Option	N/A
Keypad		15 keys, raised markings, backlit 4 function keys or touch version	Option	N/A
Audio	Buzzer		●	●
Terminal connections	USB	1 USB host	●	●
Terminal size		148x77x26 mm (5.8x3.03x1.02") 180x83x43 mm (7.08x3.26x1.69")	●	●
Weight		150 g (5.29 oz) 254 g (8.95 oz)	●	●
Environment	Operating Temperature Storage Temperature Operating Humidity	0°C to +40°C (32°F to 104°F) -20°C to +55°C (-4°F to 131°F) 85% non-condensing at +40°C (104°F)	● ● ●	● ● ●
Accessory	Privacy shield	Factory mounted Field upgradable	N/A Option	Option N/A
Security		Certified PCI PTS 5.x online & offline	●	●



www.ingenico.com

ingenico
Smart
terminals