

Move/3500

Accept any payment while on-the-go

- Leverage Telium applications on the next-generation payment terminal
- Make NFC payment a seamless consumer experience
- Bring mobile payment to your POS with the most connected terminal



security



smartcard



magstripe



contactless



connectivity



large display



TELIUM
TETRA

The Move/3500 offers a seamless payment experience while on-the-go. As a best-in-class, pocket-sized portable terminal it complies with future security standards.

Highest Security

The Move/3500 is PCI-PTS 5.x certified. Its TELIUM Tetra OS uses the latest cryptographic schemes with future-proof key length.

All Payment options

The Move/3500 enables NFC couponing and wallet use cases, in addition to EMV Chip & PIN, swipe and contactless.

User-friendly and intuitive interface

Featuring a large 3.2-inch display, the Move/3500 provides a seamless payment experience.

Designed for Mobility

Designed for indoor and outdoor use, the pocket-sized Move/3500 offers extended battery life. It is the perfect business companion for merchants.

Maximized network availability

In one single terminal, Move/3500 proposes a full spectrum wireless connectivity (with 4G, 3G, GPRS, Dual SIM, Bluetooth and WiFi), offering flexibility to merchant in the point of sale, while optimizing communication costs.

Seamless NFC payment

The Move/3500 boosts NFC payment by offering to customers a seamless experience through a dedicated card-reader zone and faster transaction flows.

Secure payment from the TELIUM Tetra OS

Backed by 30 years of experience and with its user-friendly interface, the TELIUM Tetra Operating System embeds the best security mechanisms to protect transaction privacy and leverage Ingenico's unique portfolio of payment applications.

Eco-designed products

Ingenico Group follows a proactive eco-design policy. From design to production, market launch to recycling, we strive to minimize Ingenico's environmental footprint throughout product life cycles.



NAME			Move/3500
Processor	Application & Crypto processor	Cortex A5	●
Memory	Internal	256 MB Flash, 128 MB RAM	●
	External	512 MB Flash, 512 MB RAM MicroSD up to 32GB	Option Option
OS		Telium Tetra OS	●
SIM		2 SIM	Option
SAM		2 SAM 3rd SAM	● Option
Card readers	Magstripe	ISO 1/2/3, 500K lifespan	●
	Smart card Contactless	EMV Level 1, 500K lifespan EMV Level 1 compliant	● Option
Display	Color	3.2" display, backlit, QVGA (320x240 pixels)	●
Keypad		20 keys, raised Marking, backlit	●
Audio	Buzzer		●
Data capture	GPS	GPS tracking	Option
Thermal Printer	Speed in lines/s	up to 30 lines/s	●
	Paper roll cage	58 mm width x Ø 40 mm	●
Terminal connectivity	WAN	4G and/or 3G and/or GPRS	Option
	LAN	WiFi and/or Bluetooth	Option
	Multicom	WAN + LAN	Option
Terminal connections	USB	Host & Slave	●
Battery	Power Supply	Dedicated power Jack	●
	Li-ion	2200mAh 2900mAh	● Option
Terminal size		169 x 78 x 57 mm (6.6x3.1x2.2")	●
Weight	Terminal + Battery	320 g (11 oz)	●
Environment	Operating Temperature	-10°C to +40°C (14°F to 104°F)	●
	Storage Temperature	-20°C to +55°C (-4°F to 131°F)	●
	Operating Humidity	85% non-condensing at +40°C (104°F)	●
Accessory	Privacy shield	Factory Mounted	Option
	Car Charger		Option
	Docking-station	Charger	●
		2 RS232	Option
		USB Host	Option
		USB Slave	Option
	Modem	Option	
	Ethernet 10/100 Base T	Option	
	Bluetooth	Option	
Security		PCI PTS 5.x & 4.x Online & Offline certified	●



www.ingenico.com

ingenico
Smart
terminals