

# Move/2500 C

**Accept all payment methods,  
anytime and anywhere**

- Ensure seamless payment whenever power or network fails
- Meet the merchant's needs for a robust, efficient and secure terminal
- Make NFC and QR code payments a seamless consumer experience



security



smartcard



contactless



camera



connectivity



connectivity



ethernet



color display



TELUM  
TETRA

With Move/2500 C, access to a secure and essential terminal that covers all payment methods.

**Maximum security**

The Move/2500 C is PCI-PTS 5.x certified. Its TELIUM Tetra OS uses the latest cryptographic schemes with future-proof key length.

**All payment options**

The Move/2500 C enables NFC couponing and wallet use cases, in addition to EMV Chip & PIN, swipe and contactless.

**Built-in data capture capabilities**

With its high performance camera, the Move/2500 C enables fast and reliable barcode and QR code scanning for alternative payment schemes acceptance.

**Guaranteed terminal availability**

In a single terminal, the hybrid Move/2500 C comes with wired (Ethernet, PSTN) or wireless (3G & GPRS, with Dual SIM) communication capabilities. This guarantees the acceptance of payment in both countertop and mobility use-cases.

**Seamless NFC payment**

The Move/2500 C boosts contactless payment by offering to the consumers a seamless experience through a dedicated card-reader zone resulting in a faster transaction flow.



NAME			Move/2500 C
Processor	Application & Crypto processor	Cortex A5	●
Memory		128 MB RAM, 256 MB Flash 128 MB RAM, 512 MB Flash	● Option
SIM		2 SIM	Option
SAM		2 SAM 3rd SAM	● Option
Card readers	Magstripe Smart card NFC/Contactless	ISO 1/2/3, 500K lifespan EMV Level 1, 500K lifespan EMV Level 1 compliant	● ● ●
Data capture	Camera	2M pixels, fixed focus (for barcode reading)	●
Display	Color	2.4" backlit , QVGA (320x240 pixels)	●
Keypad		16keys, raised Marking, backlit 4 Functional Keys without backlight	● ●
Audio	Buzzer		●
Thermal Printer	Speed in lines/s Paper roll cage	Up to 24 lines/s 58 mm width x Ø 40mm	● ●
Terminal connectivity	WAN	3G and / or GPRS	Option
	Wired	Dial-up Modem RJ45 Ethernet 10/100 base T RJ45	● ●
Terminal connections	USB Serial Power Supply	Micro USB Host & Slave RS 232 RJ11 Dedicated power jack	● ● ●
Battery	Li-Ion	2200mAh	●
Terminal size		215x81x69 mm (8.46x3.2x2.7")	●
Weight	Terminal + Battery	378 g (13,3 oz)	●
Environment	Operating Temperature Storage Temperature Operating Humidity	-10°C to +40°C (14°F to 104°F) -20°C to +55°C (-4°F to 131°F) 85% non-condensing at +40°C(104°F)	● ● ●
Security		PCI PTS 5.x Online & Offline certified	●



www.ingenico.com

