

Open/1500

Stealthy, powerful and scalable contactless module to fit any transport projects

- Designed for open payment by meeting transport & payment needs
- Integrated easily & sleekly in plastic embedded validator (bus, tramway, train, ferries...)
- Complies with transport & payment standards thanks to a dedicated compliant contactless reader
- Enable the latest contactless payments and new use cases such as contactless tickets, mobiles or IoT and manage closed-loop cards (Mifare,® Desfire®...)















Part of new generation of unattended devices, the Open/1500 offers the best of transport and payment worlds to meet all your open payment requirements.

Highest security

PCI PTS 5.1 certified, the Open/1500 is natively designed to meet local regulations and ensure long-term compliance.

Contactless, NFC Payment

The Open/1500 enables all contactless payments methods: Visa, Mastercard, Amex, Discover, CUP, Interact, Flash, ApplePay, GooglePay... and many more!

All ticketing media and applications

The Open/1500 is able to manage all digital tickets: closed-loop cards (Mifare, Desfire ...), NFC devices, contactless tickets, QR codes (through external optional camera), mobile apps (through Bluetooth)... Thanks to Paragon ID's expertise, provided as part of the fruitful partnership with Ingenico, the open payment terminals are able to handle all kinds of future ticketing media and new transport applications.

Compliant with transport standards

The Open/1500 is compliant with standards for use in fixed or mobile equipment (road vehicles and railways).

Easy mechanical integration in embedded validators

Thanks to its sleek design, the Open/1500 fits in a plastic validator which will be embedded in a bus, a tramway, a train or a ferry. Only the blacklit RVB and RVB LEDs are visible.

Powerful, with multiple connections

Based on the most powerful processor of Telium TETRA range with a large amount of memory, the Open/1500 has many interfaces to fit all open payment usage cases.

Highly ruggedized and durable

Thanks to its robust design (IK10) and high protection against water (IP65) the Open/1500 stands up to the most demanding indoor and outdoor environments. Thanks to the additional removable battery, the battery lifetime is extended to the device lifetime.









NAME		Open/1500
Processor	Application processor	Cortex A5
Memory	Internal External	512 MB Flash, 512 MB RAM MicroSD up to 32GB
OS		Telium TETRA
SAM		4 SAM ID-000 ISO 7816 (High Speed protocol) Studied for vibration resistance Accessible without unmount the reader
Card reader	Contactless NFC	EMV Level 1 compliant / ISO 14443 A/B/B' ISO 18 092 (card / reader / peer-to-peer modes)
Battery		Standard battery + additional removable battery
User inteface	Contactless landing zone LEDs indicator	RVB backlit landing zone 4 RVB LEDs
Maintenance interface		Maintenance button and LED
Audio	Buzzer Polyphonic sound (wav reader)	Mono Through external loudspeaker (not provided)
Terminal connections	USB Serial I/O Sound	1 x USB Slave (Micro USB connector) 1 x USB Host (Micro USB Connector) 2 x RS232 (UST connectors) 2 x inputs + 2 x outputs (isolated) 1 x 2 PIN connector for external loudspeaker
Terminal connectivity	Ethernet 10/100 Bluetooth	1 x RJ 45 BT 4.1 module (beacon mode)
Power supply	External power supply	10W 12V Wake up mode
Accessories	Provided Optional	Plastic piece for rounding the landing zone 6-pin to 2-pin connector adapter (12V PSU) JST to USB-A cables (0.5m, 1.15m, 2m) JST to DB9 serial cable (1m)
Terminal size	Overall: W x H x D mm	75.5 x 72 x 37 mm (2.9x2.8x1.5")
Weight		134g (4.7oz)
Environment	Operating temperature Storage temperature Operating humidity EMC standards	-20°C to +70°C (-4°F to 158°F) -20°C to +70°C (-4°F to 158°F) 95% non-condensing at +55°C (131°F) For fixed & mobile (road, railways) equipment
Material	Plastic	Compliant with fire & smoke standard (EN 45 545-2)
IP	Ingress protection	IP 65
IK	Shock protection	IK 10
Transportation standards		Automotive & railways certified RCTIF v5 TS:EN 16 794
Security		Certified PCI PTS 5.1 online & offline



